

**Publication number:** EP0811789

**Publication date:** 1997-12-10

**Publication date:** 1997-12-10

**Inventor:** SADA TAKASHI (JP)

**Applicant:** KOYO SEIKO CO (JP)

**Classification:**

- International: F01L1/16; F01L1/18; F16C13/00; F16C33/30;  
F01L1/14; F01L1/18; F16C13/00; F16C33/30; (IPC1-7):  
F16H53/06

**- European:** F01L1/16; F01L1/18; F16C13/00G; F16C33/30


**Application number:** EP19960938505 19961120

**Priority number(s):** WO1996JP03390 19961120; JP19950302763  
19951121; JP19950302765 19951121

**Also published as:**

WO9719278 (A1)  
US5997988 (A1)  
EP0811789 (A4)  
EP0811789 (B1)

**Cited documents:**




DE4326768  
EP0661470  
US4834400  
US5456136  
JP8232964

**Report a data error here**

## Abstract of EP0811789

A mechanical part having a rolling contact surface (11a) with many isolated minute recesses. A maximum height  $R_y$  of a roughness curve  $R$  obtained by cutting this contact surface (11a) with a plane perpendicular thereto is  $1-3 \mu m$ , and a peak height  $R_p$  with respect to the center line of the roughness curve  $R$  and a valley depth  $R_v$  with respect thereto have the relation of  $R_p/R_v \leq 0.3$ . This indicates that the contact surface (11a) has very low peaks of a relatively high distribution and very deep valleys of a relatively low distribution. Owing to the very low peaks of a relatively high distribution, a sufficiently wide contact area is secured. Owing to the valleys of a low distribution and a large depth, oil reservoirs of a sufficient capacity are formed.

FIG. 1



Data supplied from the **esp@cenet** database - Worldwide